

Witness Trees	Inches in Diameter	Bearings	Distances in Links	Witness Trees	Inches in Diameter	Bearings	Distances in Links
stone marked with +		S 34° E	64				
South. W. cor of aranda		N 65½° E	98				
B Apple tree	12	S 33° E	63				
B. walnut	10	S 41° W	54				
Poplar	12	S 89° W	54				
W. cherry	2½	N 41° W	5½				
Beach	1½	N 67½ W	13½				

Feb. 6
 1913
 I received the above article
 relative to survey of the land
 the boundary line of the land
 quarter of section twenty
 four county of, we have
 been met at the same
 in the entire the water
 the survey we decided to
 and well said survey in
 giving the following
 survey showed the land
 being short of half a
 in carrying the chain we
 survey as to plat and
 of the right place and the
 quarter by running a
 with a line of 120 ft
 foundation of the survey
 established a corner in
 line 120 ft left north
 intersection the south
 measured by apple tree
 made last of a corner
 pole of a line at the int
 of land quarter northeast
 Poplar Run 24 W 34 S
 of land quarter as well as
 line of the first quarter and
 W 34 N 34 S and line
 I have by letter the first
 survey at made by me
 with my hand and seal

Buskirk, Miller & Robinson Survey.

Jan 16
1913

A written ten days notice having been given to the interested parties to survey all lines and establish all corners necessary to establish the boundary lines of the land of Lydia Buskirk in the south west quarter of section twenty eight town nine north range one west Monroe county Ind. we Charles R. Whitaker Jacob Miller & Milton Robinson met at the residence of Wm H Buskirk as designated in the notice the weather not being favorable to proceed with the survey we decided to set Monday Jan. 13, 1913 to meet and make said survey meet as agreed upon and organized by qualifying the following helpers Sherill Hazel assistant surveyor Charlie M. Bowers flagman Haskel Turner chainman being short of help Charlie M. Bowers and myself helped in carrying the chain we then proceeded to make the following survey as to plat and notes establish a corner at the intersection of the right pike and the south line of said south west quarter by driving an iron pin witnessed by a stone marked with a cross S 34° E 54 link and the south west corner of the stone foundation of the veranda of Wm H Buskirk N $60\frac{1}{2}^{\circ}$ E 98 links established a corner in the center of the right pike said corner being 18 rods 10 ft north with the center of said pike of a point at intersection the south line of said quarter and the right pike witnessed by apple tree 12 in S 33° E 63 links established a corner 24 rods east of a corner 18 rd. 10 ft north with the center of the right pike of a corner at the intersection of said pike and the south line of said quarter witnessed by Walnut 10 in S 41° W 56 link and a Poplar 12 in S 89° W 46 $\frac{1}{2}$ links established a corner on the south line of said quarter 24 rods east of corner at the intersection of the south line of the said quarter and the right pike witnessed by W. Cherry 2 $\frac{1}{2}$ in N 41° W 5 $\frac{1}{2}$ link and back 1 $\frac{1}{2}$ in N 67° W 13 $\frac{1}{2}$ links

I hereby certify the foregoing to be a true and correct report of the survey as made by me on the above date in witness whereof I attach my hand and seal.

Charles R Whitaker

M. C. S.